


230V
50-60Hz
3p = 6h

400V
50-60Hz
4p, 5p = 6h

500V
50-60Hz
4p, 5p = 7h



Prúd Napätie Póly Krytie Hodinový uhol Typ Balenie ks Hmotnosť g/ks Rozmery strana/obr.



ISN 1632

16 A	230 V	3	IP 54	6 h	ISN 1632	12	166	20/1
16 A	400 V	4	IP 44	6 h	ISN 1643	12	181	20/1
16 A	500 V	4	IP 44	7 h	IS 1645	12	176	20/2
16 A	400 V	5	IP 44	6 h	ISN 1653	12	197	20/1



ISN 3243

32 A	230 V	3	IP 54	6 h	ISN 3232	9	270	20/1
32 A	400 V	4	IP 44	6 h	ISN 3243	9	289	20/1
32 A	500 V	4	IP 44	7 h	IS 3245	12	257	20/2
32 A	400 V	5	IP 44	6 h	ISN 3253	9	315	20/1

Bezskrútková



ISB 1653

16 A	400 V	5	IP 44	6 h	ISB 1653	12	190	20/1
32 A	400 V	5	IP 44	6 h	ISB 3253	9	340	20/1



ISG 1643

16 A	230 V	3	IP 67	6 h	ISG 1632	10	165	20/3
16 A	400 V	4	IP 67	6 h	ISG 1643	10	190	20/3
16 A	400 V	5	IP 67	6 h	ISG 1653	10	224	20/3



ISG 3232

32 A	230	3	IP 67	6 h	ISG 3232	12	298	20/3
32 A	400 V	4	IP 67	6 h	ISG 3243	12	285	20/3
32 A	400 V	5	IP 67	6 h	ISG 3253	12	324	20/3



ISGN 6353

63 A	400 V	4	IP 67	6 h	ISG 6343	10	616	20/4
63 A	500 V	4	IP 67	7 h	ISG 6345	10	670	20/4
63 A	400 V	5	IP 67	6 h	ISGN 6353	2	976	20/5



ISGN 12543

125 A	230 V	3	IP 67	6 h	ISGN 12532	2	105	20/6
125 A	400 V	4	IP 67	6 h	ISGN 12543	2	116	20/6
125 A	500 V	4	IP 67	7 h	ISGN 12545	2	116	20/6
125 A	400 V	5	IP 67	6 h	ISGN 12553	2	125	20/6
125 A	500 V	5	IP 67	7 h	ISGN 12555	2	125	20/6

Poznámka: v sortimente máme aj typy s pilotným kontaktom - označenie ISGN 125xx-p