



IVN 1632

Prúd	Napätie	Póly	Krytie	Hodinový uhol	Typ	Balenie ks	Hmotnosť g/ks	Rozmery strana/obr.
16 A	230 V	3	IP 54	6 h	IVN 1632	14	128	24/31
16 A	400 V	4	IP 44	6 h	IVN 1643	14	146	24/31
16 A	500 V	4	IP 44	7 h	IV 1645	10	160	24/33
16 A	400 V	5	IP 44	6 h	IVN 1653	14	159	24/31



IVN 3253

Prúd	Napätie	Póly	Krytie	Hodinový uhol	Typ	Balenie ks	Hmotnosť g/ks	Rozmery strana/obr.
32 A	230 V	3	IP 54	6 h	IVN 3232	10	217	24/31
32 A	400 V	4	IP 44	6 h	IVN 3243	10	235	24/31
32 A	500 V	4	IP 44	7 h	IV 3245	10	214	24/33
32 A	400 V	5	IP 44	6 h	IVN 3253	10	261	24/31

Bezskrútková



IVB 1653

Prúd	Napätie	Póly	Krytie	Hodinový uhol	Typ	Balenie ks	Hmotnosť g/ks	Rozmery strana/obr.
16 A	400 V	5	IP 44	6 h	IVB 1653	14	152	24/31
32 A	400 V	5	IP 44	6 h	IVB 3253	10	274	24/31



IVNO 1653

Prúd	Napätie	Póly	Krytie	Hodinový uhol	Typ	Balenie ks	Hmotnosť g/ks	Rozmery strana/obr.
16 A	400 V	5	IP 44	6 h	IVNO 1653	14	156	24/32
32 A	400 V	5	IP 44	6 h	IVNO 3253	10	259	24/32

Reverzačná vidlica umožňuje pootočením otočného dielu zmenu fáz.



IV 6343

Prúd	Napätie	Póly	Krytie	Hodinový uhol	Typ	Balenie ks	Hmotnosť g/ks	Rozmery strana/obr.
63 A	400 V	4	IP 44	6 h	IV 6343	12	470	24/34
63 A	500 V	4	IP 44	7 h	IV 6345	12	515	24/34